

# TX-125EN

---

## Key Specifications/Special Features:

1. Pocsag Encoder Transmitter
2. Multiple Protocol support

---

## TX-125EN Rich Sophistication:

---

- \* 16 Channels
- \* Active voltage range: DC 12V
- \* Output power up to 5 watt (HI)
- \* RS232 port for serial data and programming
- \* Support COMP1, COMP2, SCOPE, GACOMP2, TAP protocol



---

## Specifications:

---

|                     |  |
|---------------------|--|
| Model               | TX-125EN Transmitter                                   |
| Frequency           | VHF 146~170 Mhz, UHF 440~470 Mhz                       |
| Modulation Type     | F3D, F3E   |
| Channel Spacing     | 12.5KHz, 25KHz   |
| Output Power        | 5 watt / 1 watt  |
| Maximum Deviation   | ±4.5K  |
| Harmonic Radiation  | Below -36 dbm  |
| Frequency Stability | 2.5 ppm  |
| Power Supply        | DC 10V ~ 14V   |
| Current Consumption | Stand by: 100mA; TX(5W) < 2A; TX(1W) < 1A              |
| Dimension           | 65.50 (W) x 30.05 (H) x 95.00 (D) mm (Without Antenna) |
| Weight              | Approximately 245g (without Antenna)                   |