



**PD121-AN**

**Specification**

LCD Display	12.1" TFT Active Matrix Panel
Brightness	250 cd/m2
Pixel Pitch(mm)	0.3075(H)×0.3075(V) mm
Max. Resolution	800 x 600 SVGA@75Hz
Contrast Ratio	300:1
Back Light	1 CCFL
Display Area	246.0(H)×184.5(W) mm
Response Time	45ms(Typ.)
Display Colors	262,144
Viewing Angle	45°~45°(H), 10°~30°(V)
Input Signal	RGB Analog 0.7V Peak to Peak
Signal Connector	15 Pin Mini D-sub
OSD Control	Power Switch, Menu, Select (+,-),Auto
Operating Temperature	0° ~ 45° C
Storage Temperature	-20° ~ 60° C
Power Consumption	20W(Typ)
Power Supply	External 36 W Power Adapter
Safety	CE, FCC, TUV-GS, UL Compliant
Touch Screen	Resistive/Capacitive
Mounting	Wall Mount(VESA 75), Unit Arm, Robatic Arm
Dimension	304.1X243.2X142.6(mm)
Gross Weight	2.4Kg



Simon International Technology Co., Ltd.

(241) 3F-9, No. 12, Lane 609, Sec 5, Chung Hsin Rd.,

San Chung City, Taipei Hsien, Taiwan, R.O.C.

Tel : +886-2-2999-6266

Fax : +886-2-2999-6106

URL : www.simonit.com.tw



Mechanical Drawing

